



**MAGNETICS INC.**  
 343 ROUTE 295, PO BOX 348  
 CHATHAM, NY 12037  
 518 392-4000 FAX 518 392-8191  
 www.kling.com

## Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200(g).

IDENTITY (As Used on Label and List) <b>Magic Wall Magnetic Paint</b>	
Manufacturer's Name <b>Kling Magnetics, Inc.</b>	Emergency Telephone Number <b>518-392-4000</b>
Address (Number, Street, City, State, and ZIP Code) <b>PO Box 348, 343 Rt. 293, Chatham, NY 12037</b>	Telephone Number for Information <b>518-392-4000 Fax: 518-392-8191</b>
	Date Prepared <b>02/28/2017</b>

### Section 2 - Hazard(s) Identification

**Respiratory protection is not required if good ventilation is maintained. Otherwise wear NIOSH approved respirator.**  
**TLV – Ethylene Glycol 50ppm ceiling.**  
**Effect of overexposure: Skin – irritation, redness, chafing. Eyes – irritation, redness, tearing.**  
**Breathing – irritation of the respiratory tract.**  
**Swallowing – Not a normal route of introduction. Mild to moderate irritation of gastrointestinal tract, diarrhea, vomiting.**

### Section 3 – Composition/Information on Ingredients

Hazardous Components (Specific Chemical Identity; Common Name(s))		
	CAS#	mg/m3
( A ) Ethylene Glycol	107-21-1	125
( B ) Ammonium Hydrozide	1336-21-6	-
( C ) Iron Powder	7439-89-6	5
( D ) Sodium Benzoate	532-32-1	-

**Note: May also contain titanium dioxide, calcium carbonate, kaolin, silicon dioxide or other pigments classified as “nuisance dusts”. Exposure to spray mists or sanding dusts should be controlled to below 2 mg/m3 through usage of NIOSH approved dust filter respirators.**

### Section 4 - First Aid Measures

**Skin Exposure: wash with warm soapy water.**  
**Eye Exposure: Flush with water 10-15 minutes.**  
**Swallowing: (if conscious) induce vomiting. Summon medical assistance. Breathing: remove person to fresh air. If necessary administer oxygen. If breathing has stopped administer CPR.**  
**SECURE IMMEDIATE MEDICAL ASSISTANCE**

## Section 5 - Fire Fighting Measures

Flammability Classification: **Non Combustible**

HMIS Ratings: **Health: 0 Fire: 0 Reactivity: 0**

**Dried paint films are combustible. Products of combustion are toxic and may include CO, Co2, and nonnumeric materials. Use dry chemical, Co2 or water spray to cool fire exposed paint to reduce internal pressure. Wear NIOSH self contained breathing apparatus.**

## Section 6 - Accidental Release Measures

**Steps to Be Taken in Case Material is Released or Spilled**

**Small Spill:** Absorb on sand, vermiculite, etc. Scoop into containers for recovery or disposal.

**Large Spill:** Dike with earth, sand, etc. Scoop into containers for recovery or disposal by approved method.

## Section 7 - Handling & Storage

**Handle as you would any latex paint. Store in a cool (not less than 10 C/ 32 F) dry place.**

## Section 8 – Exposure Controls

**Respiratory Protection:** None is required if good ventilation is maintained. Otherwise wear NIOSH approved respirator where vapor concentrations are exceeding TLV for ethylene glycol are encountered.

**Ventilation:** Mechanical local exhaust at point of contaminant vapor, mist or dust release.

**Protective Gloves –** Impervious.

**Eye Protection-** Splashproof safety goggles (ANSI 787 1968)

**Other Protective Equipment:** Eye wash station, emergency showers.

## Section 9 – Physical and Chemical Properties

Boiling Range: **212°f**

Weight: **23 lbs./ Gallon**

Vapor Density (AIR = 1)

**Heavier than Air**

Evaporation Rate (Butyl Acetate = 1)

**Slower than Ether**

Appearance and Odor

**Light Grey in Color**

## Section 10 – Stability and Reactivity

**Stability:** Stable

**Conditions to Avoid:** Not applicable

**Incompatibility (*Materials to Avoid*):** Not applicable

**Hazardous Decomposition Products:** Thermal decomposition may yield: Co, Co2, Toxic Monomer fumes

**Hazardous Polymerization:** Will not occur.

## Section 11 - Toxicological information

Toxicological Information

**No Data Available**

## Section 12 - Ecological Information

Ecological Information

**No Data Available**

## Section 13 - Disposal Considerations

Disposal Information

**Dispose in accordance with all applicable regulations for latex paint disposal.**

## Section 14 - Transport Information

Transportation Information

**NMFC (United States National Motor Freight Classification) # 149980**

## Section 15 – Regulatory Information

Regulatory Information

**No Data Available**

## Section 16 - Other Information

Other Information

**The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients were advised to confirm in advance of need that the information is current, applicable and suitable to their circumstances**